



Series 4304/4354

Easy Remove Vinyl Film Product Information

-
- General Description:** FDC Series 4304/4354 Easy Remove Vinyl is a solid color flexible semi gloss calendered vinyl film, available in a variety of colors. This product is made for interior/exterior signage. Posters, show cards, banners and window graphics. Pressure sensitive adhesive specifically designed for high performance removable applications.
- Colors:** Available in a variety of opaque solid colors. Call your FDC sales representative for a current color selection guide.
- Thickness:** 3.0 mil. / 4.0 mil. w/adhesive
- Surface/Finish:** Semi gloss
- Application Surface:** Flat and simple curves.
- Adhesive:** Low tack removable acrylic based pressure sensitive adhesive. This allows the vinyl to adhere to the substrate and peel without adhesive residue.
- Performance:** Excellent anchorage to vinyl face stocks while maintaining removability from broad range of substrates.

Note: Always pretest material on your specific substrate.

- Liner:** 78# liner.
- Dimensional Stability:** Excellent. No measurable shrinkage on applied parts.
- Outdoor Durability:** Face film durable up to 2 years. Removability up to 1 year when properly applied and not submitted to high heat temperatures.
- Abrasion Resistance:** Face film showed good results after testing.
- Humidity Resistance:** Face film showed no negative results.
- Chemical Resistance:** Resistant to mild acids, alkalies, salts and most petroleum based oil, grease and aliphatic solvents.
- Service Temp Range:** 30°F to 140°F (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions).
- Minimum App Temp:** 40°F
- Shelf Life:** 2 year when stored at temperatures under 70°F and 50% R.H.
- Printability:** Thermal printable. Screen printable with vinyl receptive inks. Always test vinyl and inks before printing.



www.fdcfilms.com

3820 Wm Richardson Drive

South Bend, Indiana 46628

e-mail: fdcfilms@aol.com

TEL: 574-273-4400 Fax: 574-273-4500

2/17/03 BSTA



Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.



www.fdcfilms.com

3820 Wm Richardson Drive

South Bend, Indiana 46628

e-mail: fdcfilms@aol.com

TEL: 574-273-4400 Fax: 574-273-4500

2/17/03 BSTA