



### 4305 Series: Promotional Grade Dry Erase Vinyl Film

FDC series 4305 is a calendered vinyl film specially formulated for interior use with dry erase type materials. The product can be written on repeatedly, and then wiped clean with a dry tissue or dry erase cleaning fluid. To order punched material, use part number 4355.

- Film Technology:** ..... **Calendered**
- Film Thickness:** ..... **4.0 mil.**
- Color Availability:**..... **Clear (000), White (002)**
- Outdoor Durability:** ..... **N/A – Interior use only**  
(\*Durability has not been determined and will be subject to its use, maintenance and environment.)
- Adhesive:** ..... **Permanent / Clear -Acrylic**
- Adhesion:**..... **4.5 lbs/in - 24 hrs**  
(PSTC-1, 180° peel @ 12” / min, 73° F, on stainless steel.  
Typical values – individual values may vary. Test prior to use.)
- Liner:** ..... **78# Kraft**
- Application:** ..... **Flat Surfaces**  
(Wet application may cause this adhesive to cloud and is not recommended.)
- Printing:**..... **N/A**
- Chemical Resistance:** ..... **Resistant to:** alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent – **Use only chemicals and cleaners specifically designed for dry erase products .**
- Temperature:** ..... **Minimum Application Temperature is 40°F**  
(\*Temperature applies for: graphics, substrate and environment.)  
**Service Temperature Range is -40F to 180°F**
- Shelf Life:**..... **1 year - when stored at 70°F and 50% relative humidity**

**Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at [www.fdcfilms.com](http://www.fdcfilms.com).**

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.

MB