



## 7260 – Print Media: Perforated Window, Removable Adhesive

FDC series 7260 is a perforated calendered vinyl film designed for printing one-way vision window graphics. Use with FDC 7004 laminate.

\*Note: 50/50 perforation (color number 102) is DOT rated and should be used for vehicle windows.

- 
- Film Technology:** ..... **Calendered - Perforated PVC**  
**Film Thickness:** ..... **8.0 mil.**  
**Color Availability:**..... **White (102 – 50% surface / 50% perforation)**  
**White (302 – 65% surface / 35% perforation)**  
(\*black 2<sup>nd</sup> side)  
**Outdoor Durability:** ..... **2 years** - when properly processed and applied  
(\*Unprinted media durability / vertical exposure)  
**Adhesive:** ..... **Removable / Clear - Acrylic**  
(\*Clean removal up to 6 months. Removability is substrate and environmental dependant. Adhesion builds with time and age increases the likelihood of adhesive transfer during removal.)  
**Liner:** ..... **6.0 mil. PET**  
**Perforation Size:** ..... **.060” (1.5 mm)**  
**Application:** ..... **Flat Surfaces, Simple Curves**  
(\*Apply to clean and dry surface. Clean using a mild soap and water, rinse, dry glass well. Do not use ammonia or solvent-based cleaners. Do not stretch the material during application as it may cause edge lift and/or curl.)  
**Printing:**..... **Thermal Transfer, Solvent, Eco Solvent, UV Inkjet, Screen**  
(\*A print test is recommended prior to production to determine the suitability of this product given a particular printer, rip, ink type and ink set. Allow at least 24 hours for inks to dry and properly outgas prior to lamination.)  
**Chemical Resistance:** ..... **Very Good: Water, Fair: Humidity, Good: Solvent**  
**Temperature:** ..... **Minimum Application Temperature is 40°F**  
**Service Temperature is 0°F to 140°F**  
**Shelf Life:**..... **1 year** - when stored at 70°F and 50% relative humidity

**Note: for further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at [www.fdcfilms.com](http://www.fdcfilms.com).**

---

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.