



## 7123 Series– FDC® Print Media: Cast Wrap, Air Advantage™ Adhesive

FDC 7123 Series is a premium grade cast vinyl film designed for printing vehicle wraps. It offers long term durability and conformability with clean removal. This product features Air Advantage™, a repositionable opaque adhesive, which provides easy application without bubbles or wrinkles. Series 7123 is warranted for use with either Series 7006 or 7000 laminate.

Reference: Application Guide – Air Advantage™ Adhesive, FDC Limited Warranty: Vehicle Wrap Applications

---

<b>Film Technology:</b> .....	<b>Cast - PVC</b>
<b>Film Thickness:</b> .....	<b>2.0 mil.</b>
<b>Color Availability:</b> .....	<b>Gloss White (002)</b>
<b>Outdoor Durability:</b> .....	<b>7 years</b> – when properly processed and applied (*Expected Durability: unprinted media, vertical exposure and ideal conditions.)
<b>Adhesive:</b> .....	<b>Air Advantage™ / Grey</b> (*Clean removal = up to 2 years from most surfaces. Removable = up to 3 years from most surfaces with 30% or less residual adhesive. May require the use of heat and or chemicals. The use of primers and adhesion promoters may greatly increase the amount of residual adhesive.)
<b>Adhesion:</b> .....	<b>1.5 lbs/in – 15 min, 2.0 lbs/in – 24 hrs</b> (PSTC-1, 180° peel @ 12” / min, 73° F, on stainless steel. Typical values – individual values may vary. Test prior to use.)
<b>Liner:</b> .....	<b>90# Layflat</b>
<b>Application:</b> .....	<b>Flat Surfaces, Compound Curves</b> (*This product may tent when used over rivets and corrugations and will require careful application over complex curves, recessed and concave surfaces.)
<b>Printing:</b> .....	<b>Solvent, Eco Solvent, UV Curable Inkjet, Latex</b> (*A print test is recommended prior to production to determine the suitability of this product given a particular printer, rip, ink type and ink set. Allow at least 24 hours for inks to dry and properly outgas prior to lamination, cutting or application.)
<b>Chemical Resistance:</b> .....	<b>No Effect:</b> Distilled Water (24 hr), Detergent (24 hr), 10% HCL (10 min), Gasoline (1 hr), 10% Ammonium Hydroxide 10 min), SAE 20 Motor Oil (10 min), Anti-freeze (24 hr)
<b>Temperature:</b> .....	<b>Minimum Application Temperature is 55°F</b> (*Temperature applies for: graphics, substrate and environment.) <b>Service Temperature is -50°F to 225°F</b>
<b>Shelf Life:</b> .....	<b>1 year</b> - when stored at 70°F and 50% relative humidity

**Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at [www.fdcfilms.com](http://www.fdcfilms.com).**

---

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss, damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.