



2407 Series: Premium Engineer Grade Reflective Film

For proper use of this product please note the following features and explanations:

Adhesive:..... **Permanent – Clear Acrylic**

This product features a Permanent adhesive and is not considered slideable, positionable or repositionable. Due to its aggressive initial tack such actions will most likely cause damage to this material.

Application:..... **Flat Surfaces, Simple Curves, Rivets and Corrugations**

Best results are obtained when applied to flat surfaces and simple curves, but this material may be used over rivets and corrugations with careful application. Transfer tape is always recommended to limit possible damage caused by over stretching.

Temperature: **Minimum Application Temperature is 60°F**

The minimum application temperature applies for: graphics, substrate and environment. This material should be stored, processed and applied at or above the minimum temperature. Temperatures below the minimum may cause the film to become less flexible with a less aggressive adhesive. Temperatures above the minimum may cause the film to become more flexible with a more aggressive adhesive. Storing, processing or applying this material in either situation may cause material failure.

**For help with selecting the correct reflective material for your application please read:
FDC Reference Chart – Selecting a Reflective Film.**

Please contact FDC Technical Support with any other questions by calling 800-634-7523.

Note: Special instructions are provided to assist the end user in the application of this product and are given without a guarantee and do not constitute a warranty. It is the responsibility of the end user to test and qualify any procedure prior to use to determine its suitability.