

Lumina® 9009 Opaque Colors Heat Transfer Film

Lumina® 9009 Series is an opaque colored heat transfer film designed for application to textiles. This Lumina® heat transfer product features excellent weeding capability for detailed designs, hot or cold peel for fast applications and opacity for multi-layer jobs. For use on 100% polyester, 100% cotton, poly/cotton blends and acrylics. To order punched material, use part number 9059.

Film Technology: Polyurethane
 Film Thickness: 3.5 Mil
 Block out: Yes
 Outdoor Durability: N/A
 Adhesive/Color: Permanent (Heat Activated) / Clear
 Liner: Pressure Sensitive PET
 Application: 100% Polyester, 100% Cotton, Poly/Cotton Blends, Acrylic and Uncoated Nylon
 (*Test Is recommended prior to production to determine the suitability of this product given the end user's textile and Intended use.)
 Cut: Reverse
 Layer: Yes
 Preheat Garment: Yes
 Computer Cut: Yes
 Preheat Garment..... Yes
 Application Time: **8 - 10 seconds** (When layering: the first layer requires only 1 second to bond prior to applying another layer. The final layer should be pressed for the full time.)
 Temperature: 302-320°F
 Sheetable: Yes
 Pressure:..... Medium
 Shelf Life 2 Years - when stored at 70°F and 50% relative humidity
 Printing: N/A
 Peel: Hot
 Washing:..... Turn garment Inside out and machine wash using a cold setting with mild detergent. Do not bleach or dry clean. Dry at normal temperatures. Follow all garment Instructions.

Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at www.fdcfilms.com

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pre-test product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handle, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.