

Lumina[®] 9410 Medium-Strong application tape

Lumina[®] 9410 Series is a medium-strong tack application tape makes light work of transferring of our printable media 9301, 9308 and 9305 series. The backing on the adhesive surface protects logos during storage and stacking.

Film Technology: Polyurethane
Film Thickness: 3.0 Mil
Block out: No
Outdoor Durability: N/A
Adhesive/Color: Clear
Liner: No
Application: 100% Polyester, 100% Cotton, Poly/Cotton Blends, Acrylic and Uncoated Nylon.)
Cut: no
Layer: no
Preheat Garment: no
Computer Cut: no
Preheat Garment..... no
Application Time: Time recommended for what print media being used calls for
Temperature: Temperatures recommended for what print media being used calls for
Sheetable: Yes
Pressure:..... Medium
Shelf Life 1 year
Printing: N/A
Peel: What print media application recommends
Washing:..... N/A

Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at www.fdcfilms.com

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pre-test product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handle, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.
